

# ACTIVATED CARBON TOWER - TACFC

## DESCRIPTION

TACFC activated carbon towers have been developed for separating oil vapours from compressed air<sup>(1)</sup> (dry type separation). TACFC series is made from high quality carbon steel. Flow distributors ensure uniform distribution of air flow through activated carbon bed. Oil vapours as well as some other hydrocarbons are separated due to adsorption process. Super fine coalescing filter is required upstream TACFC and 1µm dust filter is recommended downstream to intercept activated carbon dust.

## APPLICATIONS<sup>(2)</sup>

- Automotive
- Electronics
- Food & Beverage
- Chemical
- Petrochemical
- Plastics
- Paint
- General industrial application

<sup>(1)</sup>For any other technical gas please contact us or your local dealer

<sup>(2)</sup>TACFC activated carbon tower can be used in variety of applications. For applications not listed please contact us or your local dealer.



## ACTIVATED CARBON TOWER RATING ACCORDING TO ISO8573-1

Solid particles	Water	Oil
-	-	0 / 1

## TECHNICAL SPECIFICATION

Operating temperature	1,5 - 50 °C	35 – 122 °F
Operating pressure	0 - 16 bar(g)	0 - 232 psi
Differential pressure	Approx. 100mbar	0,29 psi
Oil vapour content (nominal) <sup>(3)</sup>	< 0,003 mg/m <sup>3</sup>	

<sup>(3)</sup>at inlet concentration < 0,01 mg/m<sup>3</sup>, liquid content should be removed in advance by fine coalescing filtration

## MATERIALS

Housing material	Carbon steel
Fittings, Screws	Brass, Brass-zinc plated, Steel
Sealing	Teflon
Corrosion protection (internal)	Hot-dip galvanizing (on request)
Outside protection	Powder paint coated (Epoxy-polyester base)
Lubricant	Shell cassida grease RLS 2

**SIZES**


ADSORBER HOUSING	CONN. SIZE <sup>(5)</sup> [inch]	FLOW CAPACITY <sup>(4)</sup>		DIMENSIONS			ACTIVATED CARBON [kg]	VOLUME [l]	WEIGHT [kg]
		[m <sup>3</sup> /h]	[scfm]	A[mm]	B[mm]	C[mm]			
TACFC 110	G 1"	110	86	1545	350	287	10	20	45
TACFC 150	G 1"	150	117	1795	350	287	12	25	52
TACFC 200	G 1"	200	157	1550	400	318	17	36	71
TACFC 250	G 1"	250	204	1800	400	318	21	46	83
TACFC 300	G 1 ½"	300	251	1565	450	373	27	55	97
TACFC 400	G 1 ½"	400	321	1815	450	373	33	70	114
TACFC 600	G 1 ½"	590	462	1880	450	425	48	105	160
TACFC 800	G 2"	770	603	1930	650	452	61	130	201
TACFC 1000	G 2"	1000	784	1985	600	503	77	170	242

<sup>(4)</sup>Refers to 1bar(a) and 20°C at 7 barg operating pressure and inlet temperature 20°C

<sup>(5)</sup>Standard connections: inlet top left, outlet bottom right (optional connections: inlet top right, outlet bottom left)

**PRESSURE EQUIPMENT DIRECTIVE PED 2014/68/EU  
(Fluid group 2)**

TACFC 110 - 300	Category 2, Module H
TACFC 400 - 1000	Category 3, Module H



**CORRECTION FACTORS**

To calculate the correct capacity of a given tower based on actual operating conditions, multiply the nominal flow capacity by the appropriate correction factor(s).

CORRECTED CAPACITY = NOMINAL FLOW CAPACITY x C<sub>OP</sub> x C<sub>OT</sub>

**OPERATING PRESSURE**

[bar]	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
[psi]	29	44	58	72	87	100	115	130	145	160	174	189	203	218	232
C <sub>OP</sub>	0,38	0,5	0,63	0,75	0,88	1	1,13	1,25	1,38	1,50	1,63	1,75	1,88	2,0	2,13

**OPERATING TEMPERATURE**

[°C]	20	25	30	35	40	45	50
C <sub>OT</sub>	1	0,98	0,97	0,92	0,86	0,75	0,6

**MAINTENANCE**

Replace activated carbon every 12 months or sooner if required. Check residual oil content with oil indicator monthly.

INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE

	Our quality management system is certified by BUREAU VERITAS in conformity with ISO 9001:2015 Reg. number: 200285
---	--